

GEOTEXTILE FABRIC SHALL BE REINFORCED WITH AN INDUSTRIAL POLYPROPYLENE NETTING WITH A MAX SPACING OF 3/4" OR EQUAL. A HEAVY NYLON TOP SUPPORT CORD OR EQUIVALENT IS REQUIRED. FOLD FABRIC 3" OVER NYLON CORD.

OR

WIRE SUPPORT FENCE SHALL BE 14 GA MIN WOVEN WIRE WITH A MAX MESH SPACING OF 6". SECURE TOP OF GEOTEXTILE FABRIC TO TOP OF FENCE WITH STAPLES OR WIRE RINGS AT 12" OC. FOLD FABRIC 3" OVER WIRE.

GEOTEXTILE FABRIC

WOOD POSTS SHALL BE A MIN. SIZE OF 4" DIA. OR 1 1/2" X 3 1/2" EXCEPT WOOD POSTS FOR GEOTEXTILE FABRIC REINFORCED WITH NETTING SHALL BE MINIMUM SIZE OF 1 1/8" X 1 1/8" OAK OR HICKORY. LENGTH TO BE 4' -6" MIN. WITH 2'-0" MIN. DEPTH IN GROUND.

EXCAVATE A TRENCH A MIN OF 4" WIDE AND 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH. BACKFILL AND COMPACT WITH EXCAVATED SOIL.

1 SILT FENCE DETAIL

C202 1/2" = 1'-0"

TREE - SEE LANDSCAPE NOTES. PRUNE 1/5 BUT RETAIN NATURAL FORM.

DOUBLE 10 GA. GALV. WIRE, TWISTED. 3 GUYS PER TREE.

REMOVE BURLAP FROM TOP OF BALL

2" MULCH EXTENDING OVER BERM

EARTH SAUCER W/ 4" HIGH BERM

BACKFILL WITH TOPSOIL AND PEAT MOSS (3 : 1) IN 9" LAYERS

2 TREE PLANTING DETAIL

C202 N.T.S.

SHRUB - SEE LANDSCAPE NOTES. PRUNE 1/5 BUT RETAIN NATURAL FORM.

REMOVE BURLAP FROM TOP OF BALL

2" MULCH EXTENDING OVER BERM

EARTH SAUCER W/ 4" HIGH BERM

BACKFILL WITH TOPSOIL AND PEAT MOSS (3 : 1) IN 9" LAYERS

3 SHRUB PLANTING DETAIL

C202 N.T.S.

MOUNT SIGN LEVEL & FLUSH WITH TOP OF POSTS

PROJECT / BUILDING TITLE

ARCHITECT CONTRACTOR

3/4" MDO PLYWD. BACKBOARD 4'-0" x 8'-0"

4x4x10' PRESSURE TREATED WOOD POST (TYP. OF 2)

4'-0"

2'-6"

3'-6"

6"

4 SITE CONSTRUCTION SIGN

C202 1/2" = 1'-0"

NEW FIRE STATION #2 FOR
GERMANTOWN FIRE DEPARTMENT
EDISON DRIVE
GERMANTOWN, WISCONSIN 53022

05/12/00	TJV		
----------	-----	--	--

PROJECT NO.
99054A

SHEET NO.
C202



FISCHER-FISCHER-THIES, INC.
ARCHITECTS • ENGINEERS • PLANNERS
S22 W22660 BROADWAY • WAUKESHA, WISCONSIN 53186-8199
(262) 547-6969 • FAX (262) 547-6960 • E-MAIL: fft@xfpc.com